Added price in €

For model

RSPV/GSPV

per run. m

Accessories for Conveyors

Designation

Bumper rail profile

Accessories/options for RSPV, RSPV-UK and GSPV

Design

			w/o VAT
230 V Schuko socket outlet	individual, incl. holder (bracket), max. 12 pieces		per piece
	paired, positioned on opposite sides of belt, incl. holder (bracket), max. 6 pieces		per pair
230 V CEE socket outlet	individual, incl. holder (bracket), max. 12 pieces		per piece
	paired, positioned on opposite sides of belt, incl. holder (bracket), max. 6 pieces		per pair
400 V CEE socket outlet	individual, incl. holder (bracket), max. 4 pieces		per piece
	paired, positioned on opposite sides of belt, incl. holder (bracket), max. 2 pieces		per pair
Cable duct	Cable duct, on both sides, synthetic		per run. m
RCCB (Residual Current Circuit Breaker)	all conveyors except RSPV-UK with integrated cooling: for max, 12 230 V Schuko socket outlets or max. 4 400 V CEE socket outlets; RSPV-UK with integrated cooling: for max. 11 230 V Schuko socket outlets or max. 400 V 3 CEE socket outlets		
On/Off button	1 additional On/Off button (at beginning of conveyor)	RSPV/GSPV RSPV-UK	
	2 additional On/Off buttons		
	3 additional On/Off buttons		
	4 additional On/Off buttons		
Foot switch	Foot switch with isolating transformer (at end of conveyor / on switch cabinet)		

		RSPV-UK		
Drawer for patient cards	Drawer for patient cards (only possible at beginning of conveyor)			
Swing-out table for patient cards	Swing-out table for patient cards, dimensions 350 x 325 mm, mounted on right* or left* at beginning or end of conveyor * (seen from conveyor running direction from above)		per piece	
Folding table	Folding table, dimensions 600 x 400 mm, mounted on right* or left* at beginning or end of conveyor * (seen from conveyor running direction from above)			

Bumper rail profile on both sides